



offers@necksimp.pl

Necks IMP Sp. z o.o.

Tegelbruksvägen 22

821 43 Bollnäs

GÜNGA

Av stål. Fästen och bultar medföljer.

Borning i regel Ø 18 mm.

LB nummer	Passar regelprofil	Figur	H mm	L mm	Vikt kg	Tillåten kraft enligt SEN kN	Kortidsström max kA-1s
3417230	U140-200	1	485	375	22	54	50
3417240		2	785	600	38	54	50
3417250		2	1185	900	51	54	50
3417260		2	1685	1275	67	54	50
3417231	U220-330	1	485	375	22	54	50
3417241		2	785	600	38	54	50
3417251		2	1185	900	51	54	50
3417261		2	1685	1275	67	54	50
3417234	USP140-300	1	485	375	22	54	50
3417244		2	785	600	38	54	50
3417254		2	1185	900	51	54	50
3417264		2	1685	1275	67	54	50
3417232	HE140A-240A	1	485	375	21	84	50
3417242		2	800	600	37	84	50
3417252		2	1200	900	50	84	50
3417262		2	1700	1275	66	84	50
3417233	HE260A-300A	1	485	375	21	84	50
3417243		2	800	600	37	84	50
3417253		2	1200	900	50	84	50
3417263		2	1700	1275	66	84	50